

CERTIFICATE OF QUALITY

Page: 1/1
Date of issue : July 5th, 2010

1.	PRODUCT NAME REVITAL COLOR AG Microreinforced Acrylic Façade Paint
2.	GENERAL DESCRIPTION Exterior waterborne acrylic paint.
3.	COMPOSITION Water – based polymers, cellulose ether, titanium dioxide, extenders, synthetic fibres, special additives.
4.	PHYSICAL AND CHEMICAL PROPERTIES
4.1.	APPEARANCE : viscous liquid
4.2.	COLOUR : white, color shades
4.3.	DENSITY (kg/dm ³ /20°C) : app.1,60
4.4.	pH (20°C) : 9,9 – 10,0
4.5.	FLASH POINT : /
4.6.	SOLIDS CONTENT (%) : 67,0 – 70,0
4.7.	WVTR μ (-) : $\mu < 800$
4.8.	VALUE Sd (m) , d = 150 μ m : Sd < 0,12 (EN ISO 7783 – 2 , Class 1, high)
4.9.	LIQUID WATER PERMEABILITY (kg/m ² h ^{0,5}) : W _{24h} < 0,06 (EN 1062 – 3, Class 3, low)
4.10.	ADHESION TO MINERAL RENDER (N/mm ²) : > 0,30 (EN 1542)
4.11.	GLOSS : Matt (EN 13300)
4.12.	VOC : max. 12,0 g/l
5.	HAZARDS IDENTIFICATION This product is classified as NOT HAZARDOUS according to EC – directive EU 1999/45/EC.
6.	TEST REPORTS ZAG Ljubljana, Report P 12/04 – 460 – 9 , 11.06.2004 FPL Stuttgart, Report AT 026d/03 ; 17.07.2003 (reprint 25.04.2008)
7.	The document was issued with the intention to prove the quality of the product according to specific requirements.

R&D Coordination Manager
Damjan Saksida, B. Sc. Chem. Techn.


