

CERTIFICATE OF QUALITY

Page: 1/1
Date of issue : July 5th, 2010

1.	PRODUCT NAME JUBOSIL H Silicone Masonry Water Repellent
2.	GENERAL DESCRIPTION Solvent – based impregnating agent which is used for making mineral building materials water repellent.
3.	COMPOSITION Siloxanes, organic solvents.
4.	PHYSICAL AND CHEMICAL PROPERTIES
4.1.	APPEARANCE : liquid
4.2.	COLOUR : colourless
4.3.	DENSITY (kg/dm ³ /20°C) : app. 0,80
4.4.	FLASH POINT : 64° C
4.5.	SOLIDS CONTENT (%) : 9,0 – 12,0
4.6.	LIQUID WATER PERMEABILITY (kg/m ² h ^{0,5}) : W _{24h} < 0,10 (EN 1062 – 3, Class 3, low)
4.7.	GLOSS : Matt (EN 13300)
4.8.	VOC : max. 740,0 g/l
5.	HAZARDS IDENTIFICATION This product is classified as HAZARDOUS according to EC-directive EU 1999/45/EC. Xn , HARMFUL, contains naphta.
6.	TEST REPORTS /
7.	The document was issued with the intention to prove the quality of the product according to specific requirements.

R&D Coordination Manager
Damjan Saksida, B. Sc. Chem. Techn.




10