

Safety data sheet
according to 1907/2006/EC, Article 31

Revision: 14.05.2020

Version number 2

Date of the first version: 21.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** SILICATECOLOR

· **Article number:** 2.002.049

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Life cycle stages**

PW Widespread use by professional workers

C Consumer use

· **Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU19 Building and construction work

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category** PROC10 Roller application or brushing

· **Environmental release category** ERC10a Widespread use of articles with low release (outdoor)

· **Application of the substance / the mixture**

Façade paint

Dispersion paint/ Latex paint

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

JUB d.o.o.

Dol pri Ljubljani 28

1262 DOL PRI LJUBLJANI

SLOVENIA

T: + 386 1 5884 183

F: + 386 1 5884 250

E: info@jub.si

· **Further information obtainable from:**

Laura Učakar

T: +386 1 5884 185

F: +386 1 5884 227

E: laura.ucakar@jub.eu

· **1.4 Emergency telephone number:**

UK Emergency number: 999

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 14.05.2020

Version number 2

Date of the first version: 21.11.2018

Trade name: SILICATECOLOR

(Contd. of page 1)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms Void

· Signal word Void

· Hazard statements

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment Not applicable.


· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 12001-26-2	Mica substance with a Community workplace exposure limit	1-5%
CAS: 112-34-5 EINECS: 203-961-6 Reg.nr.: 01-2119475104-44	2-(2-butoxyethoxy)ethanol  Eye Irrit. 2, H319	≤1%
CAS: 9004-34-6 EINECS: 232-674-9	Cellulose substance with a Community workplace exposure limit	≤0.5%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31








Revision: 14.05.2020

Version number 2

Date of the first version: 21.11.2018

Trade name: SILICATECOLOR

(Contd. of page 2)

CAS: 1310-58-3 EINECS: 215-181-3 Reg.nr.: 01-2119487136-33	potassium hydroxide  Skin Corr. 1A, H314  Acute Tox. 4, H302	0-≤0.1%
CAS: 886-50-0 EINECS: 212-950-5	terbutryn  Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)  Acute Tox. 4, H302; Skin Sens. 1, H317	≤0.1(0.01)%
CAS: 13463-41-7 EINECS: 236-671-3	Pyrrhione zinc  Acute Tox. 3, H301; Acute Tox. 3, H331  Eye Dam. 1, H318  Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10)	≤0.1(0.005)%

· **Additional information:**

Classification and labelling of the product is prepared in accordance with the instructions of the supplier of biocidal active ingredients or biocide products.

The technology of protection active ingredients (AMME - Advanced Micro Matrix Embedding) allows changing of the classification of chemicals and this resulting in different labelling of products containing processed substances.

The total content and the content of free 2-octyl-2H-isothiazol-3-one (OIT) are indicated. Only the content of free OIT is toxicological relevant and is subject to the classification of this mixture regarding the following properties: environmental hazardous properties, skin and eye irritation, sensitisation.

The total content and the content of free zinc pyrithione (ZnPy) are indicated. Only the content of free ZnPy is toxicological relevant and is subject to the classification of this mixture regarding the following properties: environmental hazardous properties, skin and eye irritation. The total content and the content of free terbutryn are indicated. Only the content of free terbutryn is toxicological relevant and is subject to the classification of this mixture regarding the following properties: environmental hazardous properties, sensitisation.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

· **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 14.05.2020

Version number 2

Date of the first version: 21.11.2018

Trade name: SILICATECOLOR

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
In case of gas release or seepage into the ground inform responsible authorities.
Inform respective authorities in case of seepage into water course or sewage system.
In case of seepage into the ground inform responsible authorities.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Use neutralising agent.
Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 14.05.2020

Version number 2

Date of the first version: 21.11.2018

Trade name: SILICATECOLOR

(Contd. of page 4)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:**
Do not store together with oxidising and acidic materials.
- **Further information about storage conditions:**
Protect from frost.
Keep container tightly sealed.
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 12001-26-2 Mica	
WEL	Long-term value: 10* 0.8** mg/m ³ *total inhalable **respirable
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol	
WEL	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm
CAS: 9004-34-6 Cellulose	
WEL	Short-term value: 20* mg/m ³ Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable
CAS: 1310-58-3 potassium hydroxide	
WEL	Short-term value: 2 mg/m ³

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Do not eat or drink while working.

- **Respiratory protection:** Suitable respiratory protective device recommended.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 14.05.2020

Version number 2

Date of the first version: 21.11.2018

Trade name: SILICATECOLOR

(Contd. of page 5)

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Protective gloves

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses

Tightly sealed goggles

Goggles recommended during refilling

· Body protection: Use protective suit.**· Risk management measures**

It is recommended to use high-quality work clothing and protective equipment. Use only outfits that meet the following standards:

- Protective gloves that meet the criteria of BS EN 374.

- Protective goggles must comply with standard BS EN 166.

- Protective mask respirator for fine dust particles and vapors should be in accordance with BS EN 143 (full face masks).

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties**· General Information****· Appearance:**

Form:

Fluid

Colour:

Different according to colouring

· Odour:

Characteristic

· Odour threshold:

Not determined.

· pH-value at 20 °C:

10-11.4

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 14.05.2020

Version number 2

Date of the first version: 21.11.2018

Trade name: SILICATECOLOR

(Contd. of page 6)

· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	≥100 °C
· Flash point:	≥100 °C
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.4-1.44 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Solubility in / Miscibility with water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	6,000-10,000 mPas
Kinematic:	Not determined.
· Solvent content:	EU VOC (kat. A/c) 40 g/l (2010) <16.3 g/l
· Organic solvents:	≤0.9 %
· Water:	27.7 %
· VOC (EC)	1.14 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 14.05.2020

Version number 2

Date of the first version: 21.11.2018

Trade name: SILICATECOLOR

(Contd. of page 7)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

Oral	LD50	5,660 mg/kg (rat)
Dermal	LD50	4,000 mg/kg (rabbit)

CAS: 1310-58-3 potassium hydroxide

Oral	LD50	273 mg/kg (rat)
------	------	-----------------

CAS: 886-50-0 terbutryn

Oral	LD50	2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>2,200 mg/l (rat)

CAS: 13463-41-7 Pyrithione zinc

Oral	LD50	269 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
		>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>2,000 mg/l (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 14.05.2020

Version number 2

Date of the first version: 21.11.2018

Trade name: SILICATECOLOR

(Contd. of page 8)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 886-50-0 terbutryn

LC50/ 96 h	1.3 mg/l (/)
EC50/ 48 h	2.66 mg/l (daphnia)
EC50/ 168 h	0.013 mg/l (/)
NOEC / 21 dni	0.01 mg/l (/)
	1.3 mg/l (daphnia)
NOEC / 35 dni	0.84 mg/l (/)

CAS: 13463-41-7 Pyrethrin zinc

LC50	0.028 mg/l (daphnia)
EC50/ 48 h	0.05 mg/l (daphnia)
EC50/ 72 h	0.067 mg/l (/)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 14.05.2020

Version number 2

Date of the first version: 21.11.2018

Trade name: SILICATECOLOR

(Contd. of page 10)

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H301 Toxic if swallowed.
 H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

- **Recommended restriction of use**

Claims contained in this document are based on our actual knowledge at the time of revision of this document. They do not undertake the properties of the product described in terms of the legal provisions for the pledge.

Placing this document as available does not unbind the product customer from its responsibility to comply with all relevant laws and regulations applicable for this product. This is especially valid in the case of product resale or resale of its mixtures or manufactured products from other areas of law and industrial property rights of third parties. If the product described above is changed by crafting or mixing with other materials, it is not possible to transfer claims from this document onto a newly made product, unless otherwise specified. In the case of product re-packaging the customer must attach the required relevant safety information as well.

- **Department issuing SDS:**

JUB d.o.o.
 Product safety department

- **Contact:**

Laura Učakar
 laura.ucakar@jub.eu

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Revision: 14.05.2020

Version number 2

Date of the first version: 21.11.2018

Trade name: SILICATECOLOR

(Contd. of page 11)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - oral – Category 3

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

. * Data compared to the previous version altered.

GB