

CERTIFICATE OF QUALITY

Page: 1/1
Date of issue : July 5th, 2010

1.	PRODUCT NAME SILICATE SMOOTH RENDER 1.0, 1.5, 2.0 and 2.5
2.	GENERAL DESCRIPTION Exterior waterborne decorative render with equally smooth structure, which slightly reminds of fine – grain structure of scratch plaster.
3.	COMPOSITION Water – based polymers, potash water glass (potassium silicate), cellulose ether, titanium dioxide, extenders, sand, special additives.
4.	PHYSICAL AND CHEMICAL PROPERTIES 4.1. APPEARANCE : paste 4.2. COLOUR : white, color shades 4.3. DENSITY (kg/dm ³ /20°C) : 1,80 – 2,10 4.4. pH (20°C) : 9,5 – 11,5 4.5. FLASH POINT : / 4.6. SOLIDS CONTENT (%) : 82,0 – 89,0 4.7. WVTR μ (-) : $\mu < 50$ 4.8. VALUE Sd (m), d = 2,0 mm : Sd < 0,10 (EN ISO 7783 – 2 , Class 1, high) 4.9. LIQUID WATER PERMEABILITY (kg/m ² h ^{0,5}) : W _{24h} < 0,10 (EN 1062 – 3, Class 3, low) 4.10. ADHESION TO MINERAL RENDER (N/mm ²) : > 0,30 (EN 1542)
5.	HAZARDS IDENTIFICATION This product is classified as NOT HAZARDOUS according to EC – directive EU 1999/45/EC.
6.	TEST REPORTS ZAG Ljubljana, Report P 355/02 – 460 – 5 , 14.06.2004
7.	The document was issued with the intention to prove the quality of the product according to specific requirements.

R&D Coordination Manager
Damjan Saksida, B. Sc. Chem. Techn.


