



CERTIFICATE OF QUALITYPage: 1/1
Date of issue : July 5th, 2010

1. PRODUCT NAME	UNIXIL G 1.0, 1.5, 2.0 and 2.5 Siloxanised Acrylic Smooth Render
2. GENERAL DESCRIPTION	Exterior waterborne decorative render with equally smooth structure, which slightly reminds of fine – grain structure of scratch plaster.
3. COMPOSITION	Water – based polymers, cellulose ether, titanium dioxide, extenders, sand, special additives.
4. PHYSICAL AND CHEMICAL PROPERTIES	<p>4.1. APPEARANCE : paste</p> <p>4.2. COLOUR : white, color shades</p> <p>4.3. DENSITY (kg/dm³/20°C) : 1,60 – 2,00</p> <p>4.4. pH (20°C) : 9,0 – 10,0</p> <p>4.5. FLASH POINT : /</p> <p>4.6. SOLIDS CONTENT (%) : 80,0 – 85,0</p> <p>4.7. WVTR μ (-) : $\mu < 120$</p> <p>4.8. VALUE Sd (m) , d = 2,0 mm : Sd < 0,24 (EN ISO 7783 – 2 , Class 2, medium)</p> <p>4.9. LIQUID WATER PERMEABILITY (kg/m²h^{0.5}) : W_{24h} < 0,10 (EN 1062 – 3, Class 3, low)</p> <p>4.10. ADHESION TO MINERAL RENDER (N/mm²) : > 0,30 (EN 1542)</p>
5. HAZARDS IDENTIFICATION	This product is classified as NOT HAZARDOUS according to EC – directive EU 1999/45/EC.
6. TEST REPORTS	/
7. The document was issued with the intention to prove the quality of the product according to specific requirements.	<div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 40%;"> <p>R&D Coordination Manager Damjan Saksida, B. Sc. Chem. Techn.</p>  </div> <div style="width: 50%; text-align: center;">  <p>JUB d.o.o. Dol pri Ljubljani 28 SI-1262 Dol pri Ljubljani Slovenija</p> <p style="text-align: right;">10</p> </div> </div>