



CERTIFICATE OF QUALITY

Page: 1/1
Date of issue: April 14th, 2010

1.	PRODUCT NAME SLAKED LIME Interior Wall Paint
2.	GENERAL DESCRIPTION Interior lime paint intended for painting of lime – cement renders.
3.	COMPOSITION Lime.
4.	PHYSICAL AND CHEMICAL PROPERTIES 4.1. APPEARANCE : paste 4.2. COLOUR : white 4.3. DENSITY (kg/dm ³ /20°C) : app.1,20 4.4. pH (20°C) : 12,0 – 13,7 4.5. FLASH POINT : / 4.6. SOLIDS CONTENT (%) : 28,0 – 35,0 4.7. WVTR μ (-) : $\mu < 90$ 4.8. VALUE Sd (m), d = 150 μ m : Sd < 0,02 (EN ISO 7783 – 2 , Class 1, high) 4.9. ADHESION TO MINERAL RENDER : > 0,10 N/mm ² (EN 24624) 4.10. VOC : max. 1,0 g/l
5.	HAZARDS IDENTIFICATION This product is classified as HAZARDOUS according to EC-directive EU 1999/45/EC. Xi , IRRITANT, contains lime.
6.	TEST REPORTS /
7.	The document was issued with the intention to prove the quality of the product according to specific requirements. <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 45%;"> <p>R&D Coordination Manager Damjan Saksida, B. Sc. Chem. Techn.</p>  </div> <div style="width: 45%; text-align: center;">  </div> </div>