

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 01.07.2020 Version number 2 Date of the first version: 19.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: DIPI SUPER COLOR 95

· Article number: 2.001.305

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Life cycle stages

PW Widespread use by professional workers

C Consumer use

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU19 Building and construction work

- · Product category PC0 Other
- · Process category PROC19 Manual activities involving hand contact
- Environmental release category ERC10a Widespread use of articles with low release (outdoor)
- · Application of the substance / the mixture Stainer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

JUB d.o.o.

Dol pri Ljubljani 28

1262 DOL PRI LJUBLJANI

SLOVENIA

T: + 386 1 5884 183

F: + 386 1 5884 250

E: info@jub.si

· Further information obtainable from:

Laura Učakar

T: +386 1 5884 185

F: +386 1 5884 227

E: laura.ucakar@jub.eu

· 1.4 Emergency telephone number:

UK Emergency number: 999

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

GB

Revision: 01.07.2020 Version number 2 Date of the first version: 19.11.2019

Trade name: DIPI SUPER COLOR 95

(Contd. of page 1)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements

H412 Harmful to aquatic life with long lasting effects.

- · Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P273 Avoid release to the environment.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Additional information:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment Not applicable.
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 57-55-6	Propylene glycol	1-5%
EINECS: 200-338-0	substance with a Community workplace exposure limit	
Reg.nr.: 01-2119456809-23		
		Contd on maga 2

(Contd. on page 3)

Revision: 01.07.2020 Version number 2 Date of the first version: 19.11.2019

Trade name: DIPI SUPER COLOR 95

CAS: 107-21-1	ethanediol	Contd. of page 2 $0-\le 0.05\%$
EINECS: 203-473-3	♦ STOT RE 2, H373	
Reg.nr.: 01-2119456816-28	Acute Tox. 4, H302	
CAS: 55406-53-6	3-Iodo-2-propynylbutylcarbamate	≤0.05%
EINECS: 259-627-5	Acute Tox. 3, H331	
	♦ STOT RE 1, H372	
	Eye Dam. 1, H318	
	Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1,	
	H410 (M=1)	
	① Acute Tox. 4, H302; Skin Sens. 1, H317	
CAS: 3811-73-2	pyridine-2-thiol 1-oxide, sodium salt	≤0.05%
EINECS: 223-296-5	Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10)	
	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2,	
	H315; Eye Irrit. 2, H319	
CAS: 1310-73-2	sodium hydroxide	0-≤0.05%
EINECS: 215-185-5	Met. Corr.1, H290; Skin Corr. 1A, H314	
Reg.nr.: 01-2119457892-27	•	
CAS: 546-93-0	Magnesite	≤0.05%
	substance with a Community workplace exposure limit	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 4)

Revision: 01.07.2020 Version number 2 Date of the first version: 19.11.2019

Trade name: DIPI SUPER COLOR 95

(Contd. of page 3)

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.

• 6.2 Environmental precautions:

In case of seepage into the ground inform responsible authorities.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

- · Further information about storage conditions: Protect from frost.
- · Storage class: 12
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5)

Revision: 01.07.2020 Version number 2 Date of the first version: 19.11.2019

Trade name: DIPI SUPER COLOR 95

(Contd. of page 4)

· 8.1 Control parameters

· Ingre	dients with limit values that require monitoring at the workplace:
CAS:	57-55-6 Propylene glycol
WEL	Long-term value: 474* 10** mg/m³, 150* ppm
	*total vapour and particulates **particulates
CAS:	107-21-1 ethanediol
WEL	Short-term value: 104** mg/m³, 40** ppm
	Long-term value: 10* 52** mg/m³, 20** ppm
	Sk *particulate **vapour
CAS:	1310-73-2 sodium hydroxide
WEL	Short-term value: 2 mg/m³
CAS:	546-93-0 Magnesite
WEL	Long-term value: 10* 4** mg/m³
	*inhalable dust **respirable dust

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

• **Respiratory protection:** Suitable respiratory protective device recommended.

· Protection of hands:

Protective gloves

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses

Tightly sealed goggles

Goggles recommended during refilling

· Body protection: Use protective suit.

· Risk management measures

It is recommended to use high-quality work clothing and protective equipment. Use only outfits that meet the following standards:

(Contd. on page 6)

Revision: 01.07.2020 Version number 2 Date of the first version: 19.11.2019

Trade name: DIPI SUPER COLOR 95

(Contd. of page 5)

- Protective gloves that meet the criteria of BS EN 374.
- Protective goggles must comply with standard BS EN 166.
- Protective mask respirator for fine dust particles and vapors should be in accordance with BS EN 143 (full face masks).

9.1 Information on basic physical ar General Information	nd chemical properties
Appearance:	
Form:	Fluid
Colour:	Black
Odour:	Mild
Odour threshold:	Not determined.
pH-value at 20 °C:	9-10
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling ra	ınge: ≥100 °C
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	1.06-1.13 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	>1.1 %
Water:	≤74.0 %

(Contd. on page 7)

Revision: 01.07.2020 Version number 2 Date of the first version: 19.11.2019

Trade name: DIPI SUPER COLOR 95

(Contd. of page 6)

 \cdot 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rel	evant for classification:
ATE (Acu	ıte Toxicit	y Estimates)
Oral	LD50	<179,059 mg/kg (rat)
CAS: 133	3-86-4 Cai	rbon black
Oral	LD50	10,000 mg/kg (rat)
CAS: 57-	55-6 Propy	rlene glycol
Oral	LD50	2,000 mg/kg (rat)
Dermal	LD50	20,800 mg/kg (rabbit)
CAS: 107	-21-1 etha	nediol
Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	9,530 mg/kg (rabbit)
CAS: 554	06-53-6 3-	Iodo-2-propynylbutylcarbamate
Oral	LD50	1,470 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	0.67 mg/l (rat)
CAS: 3811-73-2 pyridine-2-thiol 1-oxide, sodium salt		
Oral	LD50	750 mg/kg (rat)
Dermal	LD50	700 mg/kg (rabbit)
Inhalative	LD50	1,080 mg/kg (rabbit)
	1	(Contd. on page 8

GB

Revision: 01.07.2020 Version number 2 Date of the first version: 19.11.2019

Trade name: DIPI SUPER COLOR 95

			(Contd. of page 7)
CAS: 13	310-73-2 so	dium hydroxide	
Oral	LD50	2,000 mg/kg (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:			
CAS: 55406-53-6 3-Iodo-2-propynylbutylcarbamate			
LC50/ 96 h	0.067 mg/l (/)		
EC50	0.022 mg/kg (/)		
EC50/ 48 h	0.16 mg/l (daphnia)		
CAS: 3811-73-2 pyridine-2-thiol 1-oxide, sodium salt			
LC50/ 96 h 0.00264 mg/l (/)			
EC50/ 120 h	0.0012 mg/l (/)		
CAS: 1310-7	73-2 sodium hydroxide		
LC50/ 96 h	45 mg/l (/)		

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

(Contd. on page 9)

Revision: 01.07.2020 Version number 2 Date of the first version: 19.11.2019

Trade name: DIPI SUPER COLOR 95

(Contd. of page 8)

Danger to drinking water if even extremely small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

European waste catalogue		n waste catalogue
	08 01 12	waste paint and varnish other than those mentioned in 08 01 11
	15 01 02	plastic packaging

- · Recommendation: Dispose of packaging according to regulations on the disposal of packagings.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information	n	
· 14.1 UN-Number · ADR, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
· Class	Void	
· 14.4 Packing group		
· ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Annex II		
of Marpol and the IBC Code	Not applicable.	

(Contd. on page 10)

Revision: 01.07.2020 Version number 2 Date of the first version: 19.11.2019

Trade name: DIPI SUPER COLOR 95

(Contd. of page 9)

· UN "Model Regulation": Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Following regulation was considered in the preparation of document:

Legislation on the occupational health and safety, the chemical legislation and regulations on biocidal products, regulations on classification, packaging and labeling of chemical and biocidal products and requirements on safety data sheets for chemicals and biocidal products composition, as well as regulations on the management of packaging and packaging waste and waste.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Recommended restriction of use

Claims contained in this document are based on our actual knowledge at the time of revision of this document. They do not undertake the properties of the product described in terms of the legal provisions for the pledge.

Placing this document as available does not unbind the product customer from its responsibility to comply with all relevant laws and regulations applicable for this product. This is especially valid in the case of product resale or resale of its mixtures or manufactured products from other areas of law and industrial property rights of third parties. If the product described above is changed by crafting or mixing with other materials, it is not possible to transfer claims from this document onto

(Contd. on page 11)

Revision: 01.07.2020 Version number 2 Date of the first version: 19.11.2019

Trade name: DIPI SUPER COLOR 95

(Contd. of page 10)

a newly made product, unless otherwise specified. In the case of product re-packaging the customer must attach the required relevant safety information as well.

· Department issuing SDS:

JUB d.o.o.

Product safety department

· Contact:

Laura Učakar

laura.ucakar@jub.eu

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity - oral - Category 4

Acute Tox. 3: Acute toxicity - inhalation - Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.

GB