


## CERTIFICATE OF QUALITY

Page : 1/1  
 Date of issue : September 13<sup>th</sup>, 2010

1.	<b>PRODUCT NAME</b>  JUB OFLEX MS MS sealant
2.	<b>GENERAL DESCRIPTION</b> One – component elastic sealant based on hybrid MS polymer used for sealing dilatation joints in construction.
3.	<b>COMPOSITION</b> Hybrid MS polymer , special additives.
4.	<b>PHYSICAL AND CHEMICAL PROPERTIES</b>
4.1.	APPEARANCE : paste
4.2.	COLOUR : white, grey
4.3.	DENSITY ( kg/dm <sup>3</sup> /20°C ) : app.1,46
4.4.	FLASH POINT : /
4.5.	HARDNESS SHORE A : 15 – 20 ( ISO 868 )
4.6.	CHANGE IN VOLUME ( % ) : < 1 ( ISO 10563 )
4.7.	TENSILE STRENGTH ( MPa ) : 0,40 – 0,60 ( EN 28339 )
4.8.	MODUL E 100 % ( MPa ) : 0,20 – 0,30 ( EN 28339 )
4.9.	ELONGATION AT BREAK ( % ) : 600 – 700 ( EN 28339 )
5.	<b>HAZARDS IDENTIFICATION</b> This product is classified as NOT HAZARDOUS according to EC – directive EU 1999/45/EC.
6.	<b>TEST REPORTS</b> /
7.	<b>The document was issued with the intention to prove the quality of the product according to specific requirements.</b>

R&D Coordination Manager  
 Damjan Saksida, B. Sc. Chem. Techn.

*Saksida*



JUB d.o.o.  
 Dol pri Ljubljani 28  
 SI-1262 Dol pri Ljubljani  
 Slovenija

1